

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.8

Revision Date: 02.03.2010

DOW CORNING(R) 752 ADHESIVE SEALANT CLEAR

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Trade name : DOW CORNING(R) 752 ADHESIVE SEALANT CLEAR

Company : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe

Belgium

Service : Dow Corning (Wiesbaden) Tel: +49 611237507

Fax: +49 611237601

Dow Corning (Seneffe) Tel: +32 64511156

Fax: +32 64888683

Emergency Phone Number : Dow Corning (Barry U.K. 24h)

Tel: +44 1446732350 Tel: +49 61122158 Tel: +32 64 888240

Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)

E-mail address (Safety Data

Sheet)

sdseu@dowcorning.com

Use of the : Adhesive, binding agents

substance/preparation

2. HAZARDS IDENTIFICATION

Not hazardous according to article 31 and Annex II of the EU REACH Regulation and its subsequent amendments.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone elastomer

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Triacetoxy(ethyl)silane	17689-77-9	241-677-4	2.2		R14
				C	R34
				Xn	R22
Methyltriacetoxysilane	4253-34-3	224-221-9	2.0		R14
				C	R34
				Xn	R22

4. FIRST AID MEASURES

On contact with eyes : Flush with water.

On skin contact : Flush with water.

If inhaled : Remove to fresh air.

1 of 6



According to article 31 and Annex II of the EU REACH Regulation

Version: 1.8

Revision Date: 02.03.2010

DOW CORNING(R) 752 ADHESIVE SEALANT CLEAR

On ingestion : No first aid should be needed.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : On large fires use dry chemical, foam or water spray (fog). On small fires use carbon

dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed

containers.

Unsuitable extinguishing

media

None known.

Hazards during fire fighting: None known.

Special protective

equipment/procedures

A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to

keep fire exposed containers cool.

Hazardous Combustion

Products

Thermal breakdown of this product during fire or very high heat conditions may evolve

the following decomposition products: Silica. Carbon oxides and traces of incompletely

burned carbon compounds. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear proper protective equipment.

Environmental precautions : Do not allow large quantities to enter drains or surface waters.

Methods for cleaning up : Scrape up and place in a container fitted with a lid. The spilled product produces an

extremely slippery surface.

7. HANDLING AND STORAGE

Advice on safe handling : General ventilation is recommended. Local ventilation is recommended. Avoid skin and

eye contact. Do not breathe vapour.

Advice on storage : Do not store with oxidizing agents. Keep container closed and store away from water or

moisture.

Specific uses : Refer to technical data sheet available on request.

Unsuitable packaging

materials

None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION



According to article 31 and Annex II of the EU REACH Regulation

Version: 1.8

Revision Date: 02.03.2010

DOW CORNING(R) 752 ADHESIVE SEALANT CLEAR

Engineering Controls : Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name CAS-No. Exposure Limits

Triacetoxy(ethyl)silane 17689-77-9 10 ppm TWA (CH3COOH)

25 mg/m3 TWA (CH3COOH)

Methyltriacetoxysilane 4253-34-3 10 ppm TWA (CH3COOH)

25 mg/m3 TWA (CH3COOH)

Personal protection equipment

Respiratory protection: Suitable respiratory protection should be worn if the product is used in large quantities,

confined spaces or in other circumstances where the OEL may be approached or

exceeded.

Depending on the working conditions, wear a respiratory mask with filter(s) E or use a

self-contained respirator.

The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection

supplier.

Hand protection : Chemical protective gloves should be worn: Butyl rubber. Nitrile rubber. Neoprene

rubber. Silver shield(TM). 4H(TM). Viton(TM). Regarding glove's breakthrough

time, contact your chemical protective glove supplier.

Eye protection : Safety glasses should be worn.

Skin protection : Protective equipment is not normally necessary.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

Environmental exposure

controls

Refer to section 6 and 12.

Additional information: These precautions are for room temperature handling. Use at elevated temperature or

aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form: Paste Colour: Colorless Odour: Acetic acid

Important health, safety and environmental information

Explosive properties : No



According to article 31 and Annex II of the EU REACH Regulation

Version: 1.8

Revision Date: 02.03.2010

DOW CORNING(R) 752 ADHESIVE SEALANT CLEAR

Specific Gravity : 1.04

Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Stability : Stable under normal usage conditions.

Conditions to avoid : None established.

Materials to avoid : Can react with strong oxidising agents. Cures in the presence of water or moisture,

releasing a small amount of acetic acid.

Hazardous decomposition

products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely

burned carbon compounds. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

On contact with eyes : Vapours released during curing may cause eye irritation.

On skin contact : Can irritate on prolonged or repeated contact.

If inhaled : The vapour is irritating to the mouth, nose and throat.

On ingestion : Small amounts transferred to the mouth by fingers during use should not injure.

Swallowing large amounts may cause digestive discomfort.

Other Health Hazard

Information

This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the

current physical form of the product, which is not in a respirable form.

Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION

Environmental fate and distribution

Solid material, insoluble in water. No adverse effects are predicted.

Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

Bioaccumulation : No bioaccumulation potential.

Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.



According to article 31 and Annex II of the EU REACH Regulation

Version: 1.8

Revision Date: 02.03.2010

DOW CORNING(R) 752 ADHESIVE SEALANT CLEAR

13. DISPOSAL CONSIDERATIONS

Product disposal : Dispose of in accordance with local regulations. According to the European Waste

Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal

authorities.

Packaging disposal : Dispose of in accordance with local regulations. Waste codes should be assigned by the

user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

Labelling according to EEC Directive

S-phrases : S24 Avoid contact with skin.

S51 Use only in well-ventilated areas.

National legislation / regulations

Ozone depleting

chemicals

: No ozone depleting chemicals are present or used in manufacture.



According to article 31 and Annex II of the EU REACH Regulation

Version: 1.8

Revision Date: 02.03.2010

DOW CORNING(R) 752 ADHESIVE SEALANT CLEAR

Status

EINECS : All ingredients listed, exempt or notified (ELINCS).

TSCA : All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.

AICS : All ingredients listed, exempt or notified.

IECSC : All ingredients listed or exempt.

KECL : All ingredients listed, exempt or notified.

PICCS : All ingredients listed, exempt or notified.

DSL : All ingredients listed or exempt.

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS , should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R14 Reacts violently with water., R22 Harmful if swallowed., R34 Causes burns.