Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Tectyl® CAVITY WAX NON SOLVENT

RUST PREVENTATIVE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Corrosion inhibitor.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39

3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Valvoline,	Page: 2
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/122 °F.

Additional Labelling:

EUH208 Contains Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7	Asp. Tox.1; H304	>= 25,00 - < 40,00
ALKARYL LONG CHAIN CALCIUM SULFONATE	722503-69-7	Aquatic Chronic4; H413	>= 2,50 - < 5,00
Cobalt bis(2- ethylhexanoate)	136-52-7 205-250-6	Eye Irrit.2; H319 Skin Sens.1A; H317 Repr.1B; H360F	>= 0,00 - < 0,10
Substances with a workplace exposure limit :			
Butane	106-97-8	Flam. Gas1; H220	>= 15,00 - < 25,00

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

203-448-7 01-2119474691-32-xxxx	Press. GasLiquefied gas; H280	
------------------------------------	-------------------------------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Valvoline,	Page: 4
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Water spray

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even

empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

> Remove all sources of ignition. Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Container may be opened only under exhaust ventilation

hood.

Advice on protection against

fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away

from open flames, hot surfaces and sources of ignition. Use

only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butane	106-97-8	STEL	750 ppm 1.810 mg/m3	GB EH40
		TWA	600 ppm 1.450 mg/m3	GB EH40
Cobalt bis(2- ethylhexanoate)	136-52-7	TWA	0,1 mg/m3 (Cobalt)	GB EH40

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

: Not required under normal conditions of use. Wear splash-Eye protection

proof safety goggles if material could be misted or splashed

into eyes.

Hand protection

: The suitability for a specific workplace should be discussed Remarks

with the producers of the protective gloves.

: Wear as appropriate: Skin and body protection

Impervious clothing

Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance aerosol

Colour amber

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : < 0 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0,70 g/cm3 (20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : Not applicable

SECTION 10: Stability and reactivity

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

None known.

10.5 Incompatible materials

Materials to avoid : Acids

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Remarks: No mortality observed at this dose.

Components:

COBALT 2-ETHYLHEXANOATE:

Acute oral toxicity : LD50 (Rat, female): ca. 3.129 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Components:

BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l

Exposure time: 2 h

LC50 (Rat): > 50000 ppm

Exposure time: 2 h
Test atmosphere: gas

Skin corrosion/irritation

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species: Rabbit

Result: No skin irritation

COBALT 2-ETHYLHEXANOATE:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species: Rabbit

Result: No eye irritation

COBALT 2-ETHYLHEXANOATE:

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

COBALT 2-ETHYLHEXANOATE:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1A.

Method: OECD Test Guideline 429

Remarks: Information given is based on data obtained from similar substances.

Germ cell mutagenicity

Not classified based on available information.

Components:

COBALT 2-ETHYLHEXANOATE:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Result: negative

BUTANE NORMAL:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

COBALT 2-ETHYLHEXANOATE:

Reproductive toxicity - : Clear evidence of adverse effects on sexual function and

Assessment fertility, based on animal experiments.

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Distillates (petroleum), hydrotreated light paraffinic

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10.000 mg/l

aquatic invertebrates Exposure time: 48 h

Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition
Exposure time: 72 h
Test Type: static test

Test substance: WAF

Method: OECD Test Guideline 201

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Toxicity to fish (Chronic

NOELR: Calculated >= 1.000 mg/l

toxicity)

Exposure time: 14 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates

NOEL: 10 mg/l Exposure time: 21 d

(Chronic toxicity)

Species: Daphnia (water flea)

Test substance: WAF

Method: OECD Test Guideline 211

ALKARYL LONG CHAIN CALCIUM SULFONATE

Ecotoxicology Assessment

Long-term (chronic) aquatic : May cause long lasting harmful effects to aquatic life.

hazard

Cobalt bis(2-ethylhexanoate)

M-Factor (Short-term (acute)

aquatic hazard)

Ecotoxicology Assessment

Short-term (acute) aquatic

: Acute aquatic toxicity Category 1

Long-term (chronic) aquatic

hazard

: Chronic aquatic toxicity Category 3

Butane

hazard

Toxicity to fish : Remarks: No toxicity at the limit of solubility

QSAR

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100

mg/l

Exposure time: 48 h Remarks: QSAR

Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l

> Exposure time: 96 h Remarks: **QSAR**

12.2 Persistence and degradability

Components:

Distillates (petroleum), hydrotreated light paraffinic

Biodegradability : Result: Not readily biodegradable.

> Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Cobalt bis(2-ethylhexanoate)

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Biodegradability : Result: Readily biodegradable.

Biodegradation: 60 % Exposure time: 10 d

Method: OECD Test Guideline 301B

Butane

Biodegradability : Result: Readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

12.3 Bioaccumulative potential

Components:

Butane

Partition coefficient: n-

octanol/water

: log Pow: 2,89

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23

Valvoline,	Page: 15
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

Valvoline	Page: 16
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that : Not applicable

deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic : Not applicable

pollutants

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 57).

on the radionodion (radio or).

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and

import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Other regulations : Young people under 18 years old are not allowed to work with

this product according to the EU Directive 94/33/EC on the

: Not applicable

: Not applicable

: Not applicable

protection of young people at work.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL and have annual quantity limits.

AICS Not in compliance with the inventory

ENCS Not in compliance with the inventory

KECI Not in compliance with the inventory

PICCS On the inventory, or in compliance with the inventory

Valvoline	Page: 17
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

IECSC Not in compliance with the inventory

TCSI Not in compliance with the inventory

TSCA On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Revision Date: 26.09.2018

Full text of H-Statements

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H360F May damage fertility.

H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable

to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department

('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Valvoline	Page: 18
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data

sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

Valvoline.	Page: 19
SAFETY DATA SHEET	Revision Date: 26.09.2018
	Print Date: 12.02.2019
	SDS Number: 000000184055
Tectyl® CAVITY WAX NON SOLVENT RUST PREVENTATIVE	Version: 4.0
887098	

RID : Regulation Concerning the International Transport of Dangerous Goods by Rail S-phrase: Safety phrase WGK : German Water Hazard Class