

SAFETY DATA SHEET PLASTIC STEEL PUTTY(A) RESIN.

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME PLASTIC STEEL PUTTY(A) RESIN.

PRODUCT NO. X0001

SUPPLIER ITW DEVCON

BAY 150

SHANNON INDUSTRIAL ESTATE

SHANNON CO CLARE IRELAND

T: 353(61)471299 F: 353(61)471285

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	10-30%	R43 Xi;R36/38 N;R51/53

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

HUMAN HEALTH

Preparation contains an epoxy resin, which may cause sensitisation and development of allergy.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

INHALATION

Move the exposed person to fresh air at once. Contact physician if discomfort continues.

INGESTION

Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention.

SKIN CONTACT

Remove affected person from source of contamination. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation persists.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Keep up-wind to avoid fumes. Keep run-off water out of sewers and water sources. Dike for water control.

PLASTIC STEEL PUTTY(A) RESIN.

SPECIFIC HAZARDS

By heating and fire, irritating vapours/gases may be formed.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Absorb with sand or other inert absorbent. Transfer to a container for disposal. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Use only in well-ventilated areas. Handle and open container with care. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT









PROCESS CONDITIONS

Provide eyewash, quick drench.

ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

Use protective gloves made of: Rubber or plastic.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

HYGIENE MEASURES

Keep away from food, drink and animal feeding stuffs. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving work place.

SKIN PROTECTION

Avoid contact with skin. Protection suit must be worn.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Paste

COLOUR Dark Grey

ODOUR Slight odour

SOLUBILITY Slightly soluble in water.

BOILING POINT (°C) >260 MELTING POINT (°C) n/d

RELATIVE DENSITY 2.8 20 °C VAPOUR PRESSURE <0.03 mmHg 25

pH-VALUE, CONC. SOLUTION 7.0 @ 20 °C FLASH POINT (°C) > 204

PLASTIC STEEL PUTTY(A) RESIN.

AUTO IGNITION TEMPERATURE (° >300

C)

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.

MATERIALS TO AVOID

Avoid contact with: Strong oxidising agents. Strong acids. Amines.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Acids - organic. Aldehydes.

11 TOXICOLOGICAL INFORMATION

Name EPOXY RESIN (Number average MW <= 700)

Toxic Dose 1 - LD 50 >2000 mg/kg (oral rat)

Toxic Dose 2 - LD 50 >2000 mg/kg (oral rat)

SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

Preparation contains an epoxy resin, which may cause sensitisation and development of allergy.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Avoid releasing to the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

MOBILITY

Do not discharge into drains, water courses or onto the ground.

WATER HAZARD CLASSIFICATION

WGK 2

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

WASTE CLASS

08 04 99

14 TRANSPORT INFORMATION



UK ROAD CLASS

9

REVISION DATE: 10/08/2005

PLASTIC STEEL PUTTY(A) RESIN.

PROPER SHIPPING NAME ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average

MW <= 700)

UN NO. ROAD 3082 UK ROAD PACK GR. III

ADR CLASS NO. 9 ADR CLASS Class 9: Miscellaneous

dangerous substances and

articles.

ADR PACK GROUP Ш HAZARD No. (ADR) 90 ADR LABEL NO. 9 HAZCHEM CODE 2X CEFIC TEC(R) NO. 90GM6-III RID CLASS NO. 9 **RID PACK GROUP** Ш UN NO. SEA 3082 IMDG CLASS IMDG PAGE NO. 9

IMDG PACK GR.IIIEMSF-A, S-FMFAGSee GuideMARINE POLLUTANTNo.UN NO. AIR3082ICAO CLASS9

AIR PACK GR. III

15 REGULATORY INFORMATION

LABELLING





itant Dangerous fo environment

CONTAINS EPOXY RESIN (Number average MW <= 700)

RISK PHRASES

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R43 May cause sensitisation by skin contact.

R36/38 Irritating to eyes and skin.

SAFETY PHRASES

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S28 After contact with skin, wash immediately with plenty of water.

S37/39 Wear suitable gloves and eye/face protection.

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

P5 Contains epoxy constituents. See information supplied by the manufacturer.

16 OTHER INFORMATION

REVISION DATE 10/08/2005

REV. NO./REPL. SDS GENERATED 8

DATE 11.02.2005

RISK PHRASES IN FULL

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.