

SAFETY DATA SHEET STAINLESS STEEL PUTTY (ST) HARDENER.

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME STAINLESS STEEL PUTTY (ST) HARDENER.

PRODUCT NO. X0046

SUPPLIER ITW DEVCON

BAY 150

SHANNON INDUSTRIAL ESTATE

SHANNON CO CLARE IRELAND

T: 353(61)471299 F: 353(61)471285

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
TRIETHYLENETETRAMINE	203-950-6	112-24-3	30-60%	C;R34 Xn;R21 R43 R52/53

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Causes burns. May cause sensitisation by skin contact. Harmful in contact with skin and if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xn;R21/22. C;R34. R43. R52/53.

HUMAN HEALTH

Corrosive to skin and eyes. Corrosive. Prolonged contact causes serious eye and tissue damage.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Do not breathe vapour/spray. Avoid contact with eyes. In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

INHALATION

Move the exposed person to fresh air at once. Contact physician if discomfort continues.

INGESTION

Do not induce vomiting. Drink plenty of water. Get medical attention.

SKIN CONTACT

Remove affected person from source of contamination. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation persists.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Water. Foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Keep up-wind to avoid fumes. Keep run-off water out of sewers and water sources. Dike for water control.

REVISION DATE: 10/08/2005

STAINLESS STEEL PUTTY (ST) HARDENER.

SPECIFIC HAZARDS

Avoid breathing fire vapours.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Dam and absorb spillages with sand, earth or other non-combustible material. Shovel into dry containers. Cover and move the containers. Flush the area with water.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Mechanical ventilation or local exhaust ventilation is required. Avoid contact with skin and eyes. Avoid eating, drinking and smoking when using the product. Observe good industrial hygiene practices.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT









RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Use protective gloves made of: Rubber or plastic.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

HYGIENE MEASURES

Keep away from food, drink and animal feeding stuffs. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving work place.

SKIN PROTECTION

Avoid contact with skin. Protection suit must be worn.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Viscous liquid

COLOUR Cream ODOUR Amine.

BOILING POINT (°C) 232 RELATIVE DENSITY 0.98 20 °C VAPOUR PRESSURE <0.1 mmHg pH-VALUE, CONC. SOLUTION 10.5 @ 25 °C

FLASH POINT (°C) >93

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

REVISION DATE: 10/08/2005

STAINLESS STEEL PUTTY (ST) HARDENER.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Avoid contact with oxidising agents. Avoid contact with acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire or high temperatures create: Nitrous gases (NOx). Oxides of: Carbon monoxide (CO). Carbon dioxide (CO2). Vapours/gases/fumes of: Ammonia or amines.

11 TOXICOLOGICAL INFORMATION

TOXIC DOSE 1 - LD 50

2, 000 mg/kg (oral rat)

SKIN CONTACT

Harmful in contact with skin. Causes burns. May cause sensitisation by skin contact. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

EYE CONTACT

May cause severe irritation to eyes.

HEALTH WARNINGS

Causes burns.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin absorption.

TARGET ORGANS

Prolonged or repeated contact: Liver. Kidneys. Respiratory system, lungs. Central nervous system.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Avoid release to the environment. The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

DEGRADABILITY

Do not allow ANY environmental contamination. Do not allow to enter drains, sewers or watercourses.

WATER HAZARD CLASSIFICATION

WGK 2

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

WASTE CLASS

08 04 99

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

LABELLING





Corrosive

Harmfu

CONTAINS

TRIETHYLENETETRAMINE

RISK PHRASES

R34 Causes burns.

R21/22 Harmful in contact with skin and if swallowed.
R43 May cause sensitisation by skin contact.

REVISION DATE: 10/08/2005

STAINLESS STEEL PUTTY (ST) HARDENER.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

SAFETY PHRASES

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S45 In case of accident or if you feel unwell, seek medical advice immediately (show label

where possible).

16 OTHER INFORMATION

REVISION DATE 10/08/2005

REV. NO./REPL. SDS GENERATED 5

DATE 06.01.05

RISK PHRASES IN FULL

R21 Harmful in contact with skin.

R34 Causes burns.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.